

No.SET2015-17311

MSDS Report

Client unit:

Name of sample: POWER BANK

Address:



Tested by: *Xie Lingling* Checked By: *Callan* Approved By: *Billow*

Date: Nov.27, 2015 Date: Nov.27, 2015 Date: Nov.27, 2015



Material Safety Data Sheet

Page: 2 of 6

No.SET2015-17311

Reviewed on Nov.27, 2015

1 Identification of substance

Product details

Product name: POWER BANK

Manufacturer:

Address:

Producer:

Address:

Model No.: HTD041100A

Tel: **Fax:** /

Mail:

MSDS Code: SET2015-17311

2 Composition/Data on components

Chemical characterization:

Description : (CAS#)

| Chemical Name | CAS No. | Composition (in % by weight) | EC No./ EC index/EINECS |
|---------------------------|------------|---------------------------------|----------------------------|
| Lithium Cobaltite | 12190-79-3 | 20-30% | 235-362-0 |
| Graphite Power | 7440-44-0 | 10-15% | 231-153-3 |
| Copper Foil | 7440-50-8 | 15-20% | 231-259-6 |
| Aluminum Foil | 7429-90-5 | 4-6% | 231-072-3 |
| LiPF ₆ | 21324-40-3 | 3-5% | 244-334-7 |
| Ethylene glycol carbonate | 96-49-1 | 10-15% | 202-510-0 |
| PP or PE | / | 10-20% | / |
| Shell (PC+ABS) | / | 20% | / |
| PCB | / | 5% | / |

3 Hazards identification

Emergency Overview: May explode in a fire, which could release hydrogen fluoride gas.

Use extinguishing media suitable for materials burning in fire.

Primary routes of entry:

Skin contact: NO

Skin absorption: NO

Eye contact : NO

CCIC Southern Electronic Product Testing (Shenzhen) CO., Ltd.

Add: Electronic Testing Building, No. 43 Shahe Road, Xili Jiedao, Nanshan District, 518055 Shenzhen, Guangdong, China

<http://www.ccic-set.com> Tel: 0755-86913585, 26701907 Fax: 0755-26701436



Material Safety Data Sheet

Inhalation: NO
Ingestion: NO
Symptoms of exposure:
Skin contact: No effect under routine handling and use.
Skin absorption: No effect under routine handling and use.
Eye contact: No effect under routine handling and use.
Inhalation: No effect under routine handling and use.
Reported as carcinogen: Not applicable.

4 First aid measures

Inhalation

Not a health hazard.

Eye contact

Not a health hazard.

Skin contact

Not a health hazard.

Ingestion

If swallowed, obtain medical attention immediately.

IF EXPOSURE TO INTERNAL MATERIALS WITHIN CELL DUE TO DAMAGED OUTER CASING, THE FOLLOWING ACTIONS ARE RECOMMENDED;

Inhalation

Leave area immediately and seek medical attention.

Eye contact

Rinse eyes with water for 15min.

Skin contact

Wash area thoroughly with soap and water and seek medical attention.

Ingestion

Drink milk/water and induce vomiting; seek medical attention.

5 Fire fighting measures

General Hazard:

Cell is not flammable. Combustion products include, but are not limited to Hydrogen fluoride, carbon monoxide and carbon dioxide.

**Extinguishing Media:**

Use extinguishing media suitable for the materials that are burning.

Special Fire fighting Instructions:

If possible, remove cell(s) from fire fighting area, If heated above 160°C, cell(s) may explode/vent.

Fire fighting Equipment:

Use NIOSH/MSHA approved full-face self-contained breathing apparatus (SCBA) with full protective gear.

6 Accidental release measures

On land:

Place material into suitable containers and call local fire/police department.

In water:

If possible, remove from water and call local fire/police department.

7 Handling and storage

Handling: No special protective clothing required for handling individual cells.

Storage: Store in a cool, dry place.

8 Exposure controls and personal protection

Engineering controls: Keep away from heat and open flame. Store in a cool dry place.

Personal Protection:

Respirator: Not required during normal operations. SCBA required in the event of a fire.

Eye/face protection: Not required safety practices of employer.

Gloves: Not required for handling of cells.

Foot protection: Steel toed shoes recommended for large container handling.

9 Physical and chemical properties:

General Information

State: Solid

Chemical properties:

Boiling Point: Not Applicable

Vapor Pressure: Not Applicable

Vapor Density: Not Applicable

Solubility In Water: Insoluble

Specific Gravity (H₂O = 1): Not Applicable

pH: Not Applicable



Material Safety Data Sheet

Density: Not Applicable
Nominal Voltage(Cell/Battery/Power Bank): 3.6V
Rated capacity: 10200mAh
Rate Energy: 36.72Wh

10 Stability and reactivity

Reactivity: None.

Incompatibilities: None during normal operation. Avoid exposure to heat, open flame, and corrosives.

Hazardous Decomposition Products: None during normal operating conditions. If cells are opened, hydrogen fluoride and carbon monoxide may be released.

Conditions to Avoid: Avoid exposure to heat and open flame. Do not puncture, crush or incinerate.

11 Toxicological information

This product does not elicit toxicological properties during routine handling and use

Sensitization: No

Teratogenicity: No

Reproductive toxicity: No

Acute toxicity: No

If the cells are opened through misuse or damage, discard immediately. Internal components of cell are irritants and sensitizers.

12 Ecological information

Some materials within the cell are bio-accumulative. Under normal conditions, These materials are contained and pose no risk to persons or the surrounding environment.

13 Disposal considerations

California regulated debris

RCRA Waste Code: Non-regulated

Dispose of according to all federal, state, and local regulations.



Material Safety Data Sheet

14 Transport information

Number of dangerous goods: 9

UN Number: 3480

Packaging Mark: No data.

Packaging Method: No data.

Transport Attentions:

According to the Packing Instruction 965 section II of IATA DGR 56th Edition for transportation.

According to the special provision 188 and 230 of IMDG(37-14).

The batteries should be securely packed and protected against short-circuits. Examine whether the package of the containers are integrate and tighten closed before transport. Take in a cargo of them without falling, dropping, and breakage. Prevent collapse of cargo piles. Don't put the goods together with oxidizer and chief food chemicals. The transport vehicle and ship must be cleaned and sterilized otherwise it is not allowed to assemble articles. During transport, the vehicle should prevent exposure, rain and high temperature. For stopovers, the vehicle should be away from fire and heat sources. When transported by sea, the assemble place should keep away from bedroom and kitchen, and isolated from the engine room, power and fire source. Under the condition of Road Transportation, the driver should drive in accordance with regulated route, don't stop over in the residential area and congested area. Forbid to use wooden, cement for bulk transport.

15 Regulations

OSHA Hazard communication standard (29 CFR 1910.1200)

Hazardous Non-hazardous

16 Other information:

The above information are correct, but does not contain all of the information and only used as a guide. The information in this document is based on our current knowledge, it apply to this product as for the correct safety tips. The information does not guarantee the properties of this product. Our company is not responsible for any damages caused by the products.